

# Power

## GMX Series

Global Market Standby Power Supply



- Line Interactive Ferro Technology
- Wide input voltage range of  $\pm 30\%$
- Compact packaging with light-weight Ferro
- Field programmable flash memory
- Embedded DOCSIS<sup>®</sup> monitoring option
- Built-in battery circuit breaker
- IEC style line cord

Alpha's GMX Series CableUPS<sup>®</sup> uninterruptible power supply is a cost-effective standby power supply designed for powering signal processing equipment in cable television and broadband LAN distribution systems. It provides a critical load with current-limited, regulated, AC power that is free of spikes, surges, sags and noise. The GMX's line interactive ferro topology allows it to compensate for input voltage variations of  $\pm 30\%$  while providing constant output voltage.

The GMX is an ideal solution for cable operators who need a high-quality, reliable uninterruptible power supply. Features of the GMX include optional embedded DOCSIS or ethernet status monitoring cards, a user-friendly smart display, programmable battery self-test, terminal block output connections, output taps for 63V and 87V, 150W auxiliary output terminal, external battery temperature probe, built-in chassis handle, and replaceable MOV's.



## GMX Series

### Specifications

Model:	GMX 915	GMX 915P	GMX 915E
<b>Electrical</b>			
Input Voltage (Vac):	120	240	240
Input Voltage Tolerance:	Operating: ±30% (80 to 150Vrms)	Operating: ±30% (158 to 292Vrms)	Operating: ±30% (158 to 292Vrms)
Line Return:	±25%	±25%	±25%
Nominal Input Current <sup>1</sup> :	13A	7A	7A
Input Frequency:	60Hz, ±3Hz	60Hz, ±3Hz	50Hz, ±3Hz
DC Voltage (Vdc):	36	36	36
Low DC Voltage Cutout:	1.75V/Cell	1.75V/Cell	1.75V/Cell
Output Voltage:	63/87 (Field Selectable)	63/87 (Field Selectable)	63/87 (Field Selectable)
Output Regulation, 87V TAP <sup>2</sup> :	±3%	±3%	±3%
Output Regulation, 63V TAP <sup>2</sup> :	±4%	±4%	±4%
Output Current:	15A	15A	15A
Output Frequency Stability:	60Hz, ±1Hz (Inverter Operation)	60Hz, ±1Hz (Inverter Operation)	60Hz, ±1Hz (Inverter Operation)
Waveform:	Quasisquare wave	Quasisquare wave	Quasisquare wave
<b>Battery Charging</b>			
Charge Current <sup>3</sup> :	10A		
Temperature Compensation:	-5mV/Cell/°C (Programmable)		
Constant Current Operation:	High Rate Charge to 90% Capacity		
Constant Voltage Operation:	2.40V/Cell (Typ. 7hrs)		
<b>Environmental</b>			
Operating Temperature:	-40 to 55°C/-40 to 131°F		
Humidity:	0 to 95% non-condensing		
Altitude:	0 to 3000m/0 to 10,000ft above sea level		
<b>Mechanical</b>			
Dimensions (in/mm):	7.8H x 16.8W x 11.4D/ 198 x 427 x 290	7.8H x 16.8W x 11.4D/ 198 x 427 x 290	7.8H x 16.8W x 11.4D/ 198 x 427 x 290
Weight (lb/kg):	60/27.5	60/27.5	60/27.5
Front Panel Display (LCD):	2 x 20 Character LCD	2 x 20 Character LCD	2 x 20 Character LCD
Front Panel Indicators (LED):	Output Status & Alarm	Output Status & Alarm	Output Status & Alarm
Finish:	Black, Epoxy Powdercoat	Black, Epoxy Powdercoat	Black, Epoxy Powdercoat
<b>Communication</b>			
Status Monitoring:	Optional DSM and ESM		
<b>Agency</b>			
Agency Compliance:	UL 1778/CSA C22.2, No. 107.1	UL 1778/CSA C22.2, No. 107.1	EN50091-1-2, IEC 60950
Emissions:	FCC, Class A	CB scheme CISPR 22, Class A	CB scheme and CE EN 50091-2, (CE Class A)
<b>Notes:</b>			
<sup>1</sup> Batteries fully charged			
<sup>2</sup> Output regulation at nominal input frequency. Frequency variations will proportionally affect the output voltage (i.e., a 1% reduction in frequency will result in approximately a 1% drop in output voltage)			
<sup>3</sup> Varies with input line voltage and output load.			

For contact information visit [www.alpha.com](http://www.alpha.com)

#### The Alpha Group >

North America	Europe, Middle East & Africa		Asia Pacific	Latin & South America
USA Tel: +1 360 647 2360 Fax: +1 360 671 4936	Cyprus Tel: +357 25 375 675 Fax: +357 52 359 595	Germany Tel: +49 9122 79889 0 Fax: +49 9122 79889 21	Lithuania Tel: +370 5 210 5291 Fax: +370 5 210 5292	P.R. China Tel: +852 2736 8663 Fax: +852 2199 7988
Canada Tel: +1 604 430 1476 Fax: +1 604 430 8908	Russia Tel: +7 495 925 9844 Fax: +7 495 916 1349	United Kingdom Tel: +44 1279 501110 Fax: +44 1279 659870		Contact USA office